





Thermostats

For Cold Application


Thermostats

For Cold Application






Refrigerator

Product	Model	Technical Specifications		
		Mechanical Parameters	Operating Temperatures	Electrical Rating
	Auto Defrost (or) Direct Cool	Mounting Bracket(Optional), Control shaft with spindle, Capillary(With Sleeve /W/o Sleeve), Earth Terminal (Optional), Terminals-AMP # 250 / AMP#187	Operating range from -10° to -30 °C with differential of 6 ° to 13° C. Defrost temperature range from +3° to +10°C	1(6)A 240V-250V AC,50/60Hz
	Without Defrost	Mounting Bracket(Optional), Control shaft without spindle, Capillary(With Sleeve / W/o Sleeve), Earth Terminal(Optional), Terminals-AMP # 250/AMP#187	Operating range from -10° to -30 °C with differential of 6 ° to 13° C.	1(6)A 240V-250V AC,50/60Hz
	Frost Free	Mounting Bracket(Optional), Control shaft without spindle, Capillary(With Sleeve /W/o Sleeve), Earth Terminal(Optional), Terminals-AMP # 250 / AMP # 187 Sensors - Plain capillary Tube(Gas Filled), with Bulb(C-Charge)	Operating range from 5-0° to -30 °C with differential of 6 ° to 13° C.	4(20)A 240V-250V AC,50/60Hz
	Damper	Control Shaft Without Spindle, Sensors - Capillary Tube with Bulb(C-change), Case with mounting holes, Lever, Damper & Thermostat w/o any switch	Operating range from +2° to -12 °C with differential of 11° C.	-----


Air conditioners

	Window Air Conditioners	Mounting Bracket(Optional), Control shaft without spindle, Capillary(With Sleeve /W/o Sleeve), Earth Terminal (Optional), Terminals-AMP # 250, Sensors- Plain capillary tube(Gas Filled / Bulb (C-Charge)	Operating range from +35° to +15 °C with differential of 2 to 3°C	20(80)A 240V-250V AC,50/60Hz
	Window Air Conditioners			

Commercial

Product	Model	Technical Specifications		
		Mechanical Parameters	Operating Temperatures	Electrical Rating
	Bottle Cooler	Mounting Bracket(Optional), Control shaft without spindle, Capillary(With Sleeve / W/o Sleeve), Earth Terminal(Optional), Terminals-AMP # 250 / AMP # 187, Sensors- Plain Capillary Tube(Gas Filled), Signal (Optional)	Operating range from +10° to -2.5 °C with differential of 5° C	4(20)A 240V- 250V, 50/60Hz
	Water Cooler		Operating range from +22° to +7 °C with differential of 5° C	4(20)A 240V-250V AC,50/60Hz
	Deep Freezer		Operating range from -20° to -35 °C with differential of 6°C	4(20)A 240V-250V AC,50/60Hz
	Constant Cut-In		Operating range from -10° to -35 ° C cut in +5°	4(20)A 240V-250V AC,50/60Hz
	Constant Setting		As per customer requirement	4(20)A 240V-250V AC,50/60Hz

Automobile

	Car Air Conditioners	Mounting Bracket(Optional), Control Shaft (Optional), Capillary (With Sleeve / W/o Sleeve), Earth Terminal(Optional), Terminals- AMP # 250 Sensors-Plain Capillary Tube(Gas Filled)	Operating range from 0° to 12 ° C with 4 ° C differential	4 A,12VDC
	Engine & Clutch Oil Control			



**ANNAPURNA BHASKARI
GROUP**

Corp.office : D-41, Phase - V, IDA Jeedimetla, HYDERABAD - 500 055. A.P., INDIA.

P : +91 40 23097637/23095371, F : +91 40 23096492 , E : info@annapurnabhaskari.com, www.annapurnabhaskari.com