
















Solenoid Valves

Bhaskari Aqua Products Pvt. Ltd.

Product	Model	Description	Voltage	Inlet/Outlet Configuration	Mounting	Flow rate in LPM
	ES 90/88	Single Way 90°(In-let)	6,12,24,36, 48VDC& 120&220VAC	G3/4" BSP(In-let) ø10.5/12mm(Out let)	Provision for Metal Bracket	1-20lpm±15%(In-let) & 25%(Out-let)
	ES 90/88 W/M	Single Way 90°(In-let)	6,12,24,36,48VDC& 120&220VAC	G3/4" BSP(In-let) ø16 mm(Out-let)	Self Mounting With M4 Nuts.	1-20lpm±15% (In-let)& 25%(Out-let)
	ES 90/88	Single Way 90°(In-let)	6,12,24,36,48VDC& 120&220VAC	G3/4" BSP(In-let) Ø10.5/12mm(Out-let)	Provision for Metal Bracket	1-20lpm±15%(In-let) & 25%(Out-let)
	ES180/88	Single Way 180°(In-let)	6,12,24,36,48VDC& 120&220VAC	G3/4" BSP (In-let) Ø10.5/12mm(Out-let)	Provision for Metal Bracket	1-20lpm ±15%(In-let) & 25%(Out-let)
	ES180/88	Single Way 180°(In-let)	6,12,24,36,48VDC& 120&220VAC	G3/4" BSP(In-let) G 1/4" BSP (Out-let)	Provision for Metal Bracket	1-20lpm ±15%(In-let) & 25%(Out-let)
	ES180/88	Single Way 180°(In-let)	6,12,24,36,48 VDC & 120&220VAC	G3/4" BSP(In-let) Ø10.5/12mm(Out-let)	Snap Fit	1-20lpm ±15%(In-let) & 25%(Out-let)
	ES180/88 W/M	Single Way 180°(In-let)	6,12,24,36, 48VDC & 120&220VAC	G3/4" BSP(In-let) Ø16mm(Out-let)	Provision for Metal Bracket	1-20lpm ±15%(In-let) & 25%(Out-let)

Product	Model	Description	Voltage	Inlet/Outlet Configuration	Mounting	Flow rate in LPM
	180/88 Screwed RO	Single Way 180°(In-let)	6,12,24,36, 48VDC & 120&220VAC	Dia 6mm (Both In-let & Out-let)	Self Mounting	UPTO 8 LPM
	Two-Leg	Single Way 180°(In-let)	6,12,24,36, 48VDC & 120&220VAC	1/4" BSP (Both In-let & Out-let)	Self Mounting	UPTO 8 LPM
	Four-Leg	Single Way 180°(In-let)	6,12,24,36, 48VDC & 120&220VAC	1/4" BSP (Both In-let & Out-let)	Self Mounting	UPTO 8 LPM
	Direct Valve	Single Way 180°	6,12,24,36, 48VDC& 120&220VAC	1/4" BSP (Both In-let & Out-let)	Self Mounting	UPTO 8 LPM
	ED 180/88	Two Way 180°(One In-let,Two Out-lets)	6,12,24,36, 48VDC& 120&220VAC 120&220VAC	G3/4" BSP(In-let) Ø10.5/12mm(Out-let)	Provision for Metal Bracket	1-20lpm±15%(In-let) & 25%(Out-let)
	ED 180/88	Two Way 180°(One In-let,Two Out-lets)	6,12,24,36, 48VDC& 120&220VAC 120&220VAC	G3/4" BSP (In-let) Ø10.5/12mm (Out-let &Out-let)	Snap Fit	1-20lpm±15%(In-let) & 25%(Out-let)
	ET 180/88	Three Way 180/88 (One In-let& 3 Out-let)	6,12,24,36, 48VDC& 120&220VAC 120&220VAC	G3/4" BSP (In-let) Ø10.5/12mm(Out-let)	Provision for Metal Bracket	1-20lpm±15%(In-let) & 25%(Out-let)



**ANNAPURNA BHASKARI
GROUP**

Corp.office : D-41, Phase - V, IDA Jeedimetla, HYDERABAD - 500 055. A.P., INDIA. P : +91 40 23097637/23095371 F : +91 40 23096492 E : info@annapurnabhaskari.com, www.annapurnabhaskari.com